

CATSE UTP ASSEMBLED OUTLETS

Technical information



Features:

- Fully assembled outlets, including faceplate, module(s) and blanks (where necessary)
- ◆ Cat5e compliant performance
- ♦ 568B wiring
- Top, bottom or rear cable entry

- ◆ 110 or LSA punch down
- ♦ Only 8mm projection behind faceplate
- ♦ Cable strain relief facility
- ◆ Protected labelling facility
- ♦ 25 year Ultima System Warranty

Materials

Faceplate, Fascia & RJ45 Jack Housing	ABS UL94V-0
RJ45 Jack Contact	Phosphor bronze, nickel plated, finished with 50μ gold plating on plug contact area
IDC Contact	Phosphor bronze, tin plated
Shutter	ABS UL94-HB

Performance

Insertion Force	20N max.
Retention Strength	7.7kg between Jack and Plug
Operating Temperature	-10°C to 60°C
Mating Cycles	750 cycles min.
IDC Wire Range	23-26 AWG stranded or solid wire. Compatible with 110 and LSA punch down tools







Part Numbers

Item	Description	Туре	Ports	Colour
777958	Assembled Outlet Cat5e Flat	Unshielded	1	White
777961	Assembled Outlet Cat5e Flat	Unshielded	2	White
783213	Assembled Outlet Cat5e Flat	Unshielded	4	White