LC-SC OS2 DUPLEX PATCH LEADS

Technical information



Ultima fibre optic patch leads are manufactured to the highest standards and supplied individually bagged with their own test certificate. The transmit and receive leg of each duplex lead is clearly marked to allow for a quick install.

Features:

Performance & Characteristics

Max Attenuation (dB) 1310nm	0.4
Max Attenuation (dB) 1550nm	0.3
Max Chromatic Dispersion (ps/nm x km) @ 1310nm	3.0
Max Chromatic Dispersion (ps/nm x km) @ 1550nm	18.0
Temperature Range	-40°C to 75°C

Physicals

Diameter (mm)	2.0
Housing Colour	Blue

Standards

LC Connector Standard	IEC 61754-20
SC Connector Standard	IEC 61754-4



LC-SC OS2 DUPLEX PATCH LEADS

Technical information



Part Numbers

	Item	Description	Mode	Length	Colour
OS2 9/125μm	798426	Fibre Patch Lead LC-SC	SM	0.5Mtr	Yellow
	779755	Fibre Patch Lead LC-SC	SM	1Mtr	Yellow
	801026	Fibre Patch Lead LC-SC	SM	1.5Mtr	Yellow
	779756	Fibre Patch Lead LC-SC	SM	2Mtr	Yellow
	801027	Fibre Patch Lead LC-SC	SM	2.5Mtr	Yellow
	779757	Fibre Patch Lead LC-SC	SM	3Mtr	Yellow
	779758	Fibre Patch Lead LC-SC	SM	5Mtr	Yellow
	800275	Fibre Patch Lead LC-SC	SM	7Mtr	Yellow
	779759	Fibre Patch Lead LC-SC	SM	10Mtr	Yellow
	800276	Fibre Patch Lead LC-SC	SM	12Mtr	Yellow
	782302	Fibre Patch Lead LC-SC	SM	15Mtr	Yellow
	782303	Fibre Patch Lead LC-SC	SM	20Mtr	Yellow
	796845	Fibre Patch Lead LC-SC	SM	25Mtr	Yellow
	800759	Fibre Patch Lead LC-SC	SM	30Mtr	Yellow