CAT5e U/UTP PVC PATCH LEADS

Technical information



Features:

- Slimline moulded strain relief boot
- Anti-snag latch
- Tested to Cat5e ANSI/TIA-568-C.2 & ISO 11801
- PVC sheath

- ♦ Slimline 4.4mm cable diameter
- ♦ Available in 11 different colours
- ◆ Available in a wide range of lengths
- Individually bagged

Construction

Sheath Material	PVC
Conductors	Stranded bare copper, 26AWG
Plugs	Unshielded RJ45 (8P8C) with gold plated contacts
Strain Relief	Slimline moulded with anti-snag latch
Wiring Scheme	T568B



Part Numbers

Length	Grey	Blue	Black	White	Red	Yellow	Green	Orange	Lt Blue	Purple	Pink
0.25m	786795	790253	792691	792692	790250	792653	792651	790255		792520	792652
0.5m	772189	772098	776686	776679	772093	772108	772103	776693	802340	776700	792654
0.75m	779491	779493			779492						
1m	772190	772099	776687	776680	772094	772109	772104	776694	801653	776701	779725
1.5m	775863	774851	776688	776681	776355	775875	776356	776695	802342	776702	792656
2m	772191	772100	776689	776682	772095	772110	772105	776696	801654	776703	779726
3m	772192	772101	776690	776683	772096	772111	772106	776697	801655	776704	779727
4m	781937	790247	790276		790252	790286	790258		802343		
5m	772193	772102	776691	776684	772097	772112	772107	776698	801656	776705	786801
6m	791758		790281								2
7m	782033	783184	790287		781938	783185	790264		802344	789393	2
8m	790283		790270								
10m	772404	772407	776692	776685	772405	772408	772406	776699	801657	776706	790279
15m	775864	781941	781944	781943	781939	781942	781940	790063		789394	
20m	775865	790248	790288	790295	775868	790291	775871				
25m	783115		783127								
30m	783116		783128		783118						