

ST-ST OM3 DUPLEX PATCH LEADS



Technical Information

Features:

- ◆ Provides moveable links between sections of permanently installed horizontal cable
- ◆ Suitable for use in computer rooms, data centres and work areas
- ◆ LSZH jacket
- ◆ Tight buffered fibre with aramid yarn strength elements
- ◆ Full test certificate provided with each lead
- ◆ High quality build and performance
- ◆ Strain relief boots to protect fibre
- ◆ Dust caps provided to keep the connector end face clean
- ◆ Marked transmit and receive legs
- ◆ RoHS compliant construction

Performance & Characteristics

Max Attenuation (dB) 850nm	3.5
Max Attenuation (dB) 1300nm	1.5
Bandwidth OFL (MHz x km) @ 850nm	1,500
Bandwidth OFL (MHz x km) @ 1300nm	500
Insertion Loss (dB)	≤ 0.20
Return Loss	≥ 35
Temperature Range	-40°C to 75°C

Standards

ST Connector Standard	IEC 61754-4
-----------------------	-------------

Physicals

Diameter (mm)	2.0
Housing Colour	Silver



Part Numbers

	Item	Description	Mode	Length	Colour
OM3 50/125µm	777064	Fibre Patch Lead ST-ST	MM	1Mtr	Aqua
	777065	Fibre Patch Lead ST-ST	MM	2Mtr	Aqua
	777066	Fibre Patch Lead ST-ST	MM	3Mtr	Aqua
	777067	Fibre Patch Lead ST-ST	MM	5Mtr	Aqua
	777068	Fibre Patch Lead ST-ST	MM	10Mtr	Aqua