



CAT6 UTP ASSEMBLED OUTLETS



Technical information

Features:

- ◆ Fully assembled outlets, including faceplate, module(s) and blanks (where necessary)
- ◆ Cat6 compliant performance
- ◆ 568B wiring
- ◆ Top, bottom or rear cable entry
- ◆ Dual block 110/LSA punchdown
- ◆ Only 8mm projection behind faceplate
- ◆ Cable strain relief facility
- ◆ Protected labelling facility
- ◆ 25 year Ultima System Warranty

Materials

Faceplate, Fascia & RJ45 Jack Housing	ABS UL94V-0
RJ45 Jack Contact	Material: Phosphor bronze, nickel plated. Finish: 50 micron gold plated on plug contact area
IDC Contact	Phosphor bronze, tin plated
Shutter	ABS UL94-HB

Performance

Insertion Force	20N max.
Retention Strength	7.7kg between Jack and Plug
Operating Temperature	-10°C to 60°C
Mating Cycles	750 cycles min.
IDC Wire Range	23-26 AWG stranded or solid wire. Compatible with 110 and LSA punch down tools



Part Numbers

Item	Description	Faceplate	Type	Modules	Colour
792389	Assembled Outlet Cat6	Bevelled Single Gang	Unshielded	1x Euro	White
792390	Assembled Outlet Cat6	Bevelled Single Gang	Unshielded	2x Euro	White
819423	Assembled Outlet Cat6	Bevelled Double Gang	Unshielded	4x Euro	White